

I. Amendments to the Claims

Please amend the claims as follows with the following
clean versions of the claims in accordance with 37 CFR §
1.121; marked-up versions of the claims are presented in the
5 following section.

Clean version of amended claims:

1. A method of enabling a client terminal user to access target resources managed by a set of resource managers within an enterprise computing environment, comprising:
 - 5 authenticating the user to establish a user primary identity;
 - mapping the user primary identity to a set of user secondary identities;
 - 10 authenticating the user to the resource managers using the set of user secondary identities;
 - following authentication using the set of user secondary identities, forwarding resource requests to the resource managers; and
 - 15 returning replies received from the resource managers back to the user.
2. The method as described in claim 1 wherein the user primary identity is mapped to the set of user secondary identities by a sign-on service.
- 20 3. The method as described in claim 2 further including the step of authenticating a trusted server to the sign-on service prior to mapping the user primary identity to the set of user secondary identities.
- 25 4. The method as described in claim 3 wherein the trusted server is authenticated to the sign-on server before the step of authenticating the user to establish the user primary identity.
- 30 5. The method as described in claim 3 wherein the trusted server is authenticated to the sign-on service after the step

of authenticating the user to establish the user primary identity.

5 6. The method as described in claim 3 wherein the user is authenticated to establish the user primary identity using an authentication service associated with the trusted server.

10 7. The method as described in claim 1 further including the step of load balancing resource requests across a set of instances of a given resource manager.

15 8. The method as described in claim 1 wherein the client terminal user accesses the enterprise computing environment over the Internet.

20 9. The method as described in claim 1 wherein the user is authenticated to a given resource manager using an authentication service associated with the given resource manager.

-
10. (Amended) A method for enabling a client terminal user to access target resources managed by a set of resource managers operative within an enterprise computing environment, wherein the environment has an associated sign-on service,
- 5 comprising:
- responsive to a request received from a user of the client terminal, authenticating the user to establish a user primary identity;
- a/ using the user primary identity, accessing the sign-on
- 10 service to retrieve a set of stored user authentication information, wherein the stored user authentication information comprises a set of user secondary identities;
- performing a sign-on to the set of resource managers using the retrieved set of user secondary identities; and
- 15 forwarding the request to a given resource manager; and
- forwarding a reply received from the given resource manager back to the user.
-

11. A method for enabling a client terminal user to access target resources managed by a set of resource managers operative within an enterprise computing environment, wherein the environment has an associated sign-on service, comprising:
- 5 having the client terminal user perform a primary logon to an intermediary server to establish a user primary identity;
- having the intermediary server pass the user's primary identity to the sign-on service and, in response, obtaining a
- 10 set of user secondary identities that may be used in enabling the intermediary server to represent the client terminal user to the resource managers;
- having the intermediary server perform a secondary logon to a first resource manager using a first user secondary
- 15 identity;
- having the intermediary server perform a secondary logon to a second resource manager using a second user secondary identity;
- having the intermediary server perform resource requests
- 20 at the first and second resource managers under the respective secondary identities; and
- forwarding responses back to the client terminal user.

12. (Amended) An enterprise computing environment having a set of resource managers and a sign-on service, the enterprise computing environment comprising:

- a2
- 5 means for authenticating a user to establish a user primary account associated with a user primary identity;
means for cooperating with the sign-on service to map the user primary account to a set of user secondary accounts associated with a set of user secondary identities;
10 means for logging onto the set of resource managers using the user secondary accounts; and
means for passing resource requests from the user to the resource managers under the user secondary accounts.

13. (Amended) The enterprise computing environment as
15 described in claim 12 wherein the server passes replies to the resource requests back to the user.

14. (Amended) A server for use in an enterprise computing environment having a set of resource managers and a sign-on service, comprising:

- a2
- 5 means for authenticating a user to establish a user primary account associated with a user primary identity;
- means for authenticating the server to the sign-on service;
- 10 means for logging onto the set of resource managers using a set of user secondary accounts returned from the sign-on service, wherein the set of user secondary accounts is associated with a set of user secondary identities; and
- means for passing resource requests and associated replies between the user and the resource managers.
-

- 15 15. The server as described in claim 14 further including means for load balancing resource requests passed to a set of instances of a given resource manager.

16. (Amended) A system, comprising:

a set of resource managers;

a sign on service;

a server, comprising:

a3 5 means for authenticating users to establish user primary accounts associated with user primary identities;

10 means for logging a given user onto the set of resource managers using a set of user secondary accounts for the given user retrieved from the sign on service, wherein a set of user secondary accounts for a given user is associated with a set of user secondary identities for a given user; and

means for passing resource requests and associated replies between the given user and the resource managers.

15 17. The system as described in claim 16 wherein at least one resource manager comprises a set of instances.

18. The system as described in claim 17 wherein the server further includes means for load balancing resource requests
20 across the set of instances.

19. The system as described in claim 16 wherein the server comprises a set of instances.

25 20. The system as described in claim 19 further including a manager that manages the set of server instances.

21. (Amended) A computer program product in a computer-useable medium executable in a processor of a server, comprising:

- at 5 means for authenticating a user to establish a user primary account associated with a user primary identity;
means for authenticating the server to a sign-on service;
means for logging onto a set of resource managers using a set of user secondary accounts returned from the sign-on service, wherein the set of user secondary accounts are
10 associated with a set of user secondary identities; and
means for passing resource requests and associated replies between the user and the resource managers.
-